



Type **A** without handle
 Type **D** with revolving handle

Mode **S** scale 0...90, 100 graduations
 (for execution with collet Z only)

d ₁	d ₂ H8			d ₃	d ₄	d ₅	b-0,5	h	l ₁	l ₂	Ø Handle
	Bore without keyway	with keyway	with collet								
52	B 10	K 10	Z 10	50	37	39,5	13	3,8	23	17	13
62	B 10	K 10	Z 10	60	47	49,5					14

1.4

Specification

Aluminium
 black anodized
 Hub cover plastic
 light grey
 Revolving handles GN 599.5
 Plastic (Technopolymer)
 black Page 61
 Keyway P9
 DIN 6885/1 Page 882
 ISO-Fundamental
 Tolerances Page 888

Information

Control knobs GN 736.1 (photo page 179) are used for setting operations with low torque.

Coarse setting is made by means of the cylindrical handle (fingertip grip) followed by fine setting using the knurled rim of the knob.

All control knobs are produced with an ergonomically shaped and attractively designed rim.

The model fitted with collet offers an absolutely reliable mounting on the shaft and at the same time allows an easy setting of the adjustable scale ring wheel.

The scale is wear resistant and easily legible since the engraved alu coloured numbers contrast with the black anodized surface. Page 338 of the catalogue gives full details of the available graduations, numbering sequence, number position and type of scale.

How to order

Control knob GN 736.1-62-B10-A

Code No.	d ₁	Bore code	d ₂	Type	Mode

Control knob GN 736.1-52-Z10-D-S

Code No.	d ₁	Bore code	d ₂	Type	Mode	Mode