

## **Aluminum Profiles**

i-Modular System, with Open Slots on All Sides, Profile Type Light











30x60 / 40x80






60x60 / 80x80



V	2	3	6		7					
S <sub>1</sub>	S <sub>2</sub>	n	Length I +1,5mm in meters		Bundle Pieces	d	k	S <sub>3</sub>	t	Grid size
30	30	6	2	3	4	5	-	3	9,75	30
30	60	6	2	3	2	5	30	3	9,75	30
40	40	8	2	3	4	6,8	-	4,5	12,25	40
40	80	8	2	3	2	6,8	40	4,5	12,25	40
60	60	6	2	3	1	5	30	3	9,75	30
80	80	8	2	3	1	6,8	40	4,5	12,25	40

## **Specification**





• RoHS

## Accessory

- T-Nuts GN 50i → Page QVX
- Cover Caps GN 60i → Page QVX
- Cover and Edging Profiles GN 70i

→ Page QVX

- Cover Profiles GN 71i → Page QVX
- Transport and Base Plates GN 80i

→ Page QVX

## Information

Aluminum profiles GN 10i are produced by extrusion molding. They can be used, for example, to easily construct protective enclosures, workplace equipment or jigs.

Aluminum profiles in combination with the removable and reusable accessories form a flexible modular system. Attachments can be fastened to either the slots or the end faces via the holes.

The profile type light is typically used for small loads or for weightoptimized constructions.

Aluminum profiles are supplied in bundles. The table shows the quantity included in each bundle.











00

ന

6

3.9

