



**2 Type**

- A Without seals
- B With seals

**3 Identification no.**

- 4 With 2 stainless steel cap nuts DIN 917

<b>d<sub>1</sub> - d<sub>2</sub></b>		<b>b</b>	<b>d<sub>3</sub></b>	<b>d<sub>4</sub></b>	<b>k</b>	<b>l<sub>1</sub></b>	<b>m</b>	<b>z</b>	<b>Accessory</b>	
One-Axis System <b>GN 132.15</b> with sleeve bearing	Two-Axis System <b>GN 132.25</b> with sleeve bearing			Mounting screws on the drive key	Clamping length			Screw locations	Recom. hand lever GN 911.3 for <b>z</b> l <sub>2</sub>	
G30 - B30	G30 - G30	22	37	M 4	40	104	33	M 8	63	78
G50 - B50	G50 - G50	30	60	M 6	65	150	53	M 10	78	92

**Specification**

- Stainless steel AISI CF-8 Matte shot-blasted
- Sleeve bearing Plastic (PTFE)
- Carriage bolt DIN 603 Stainless steel
- Cap nuts DIN 917 / Washers Stainless steel
- Seals
  - Sealing disks Plastic (Polyacetal POM)
  - Spacer ring Silicon, 40 ... 60 Shore A
- *Plastic Characteristics* → Page 2158
- *Stainless Steel Characteristics* → Page 2166
- RoHS

**Accessory**

- Adjustable Hand Levers GN 911.3 → Page 1785

**Information**

Two-way linear actuator connectors GN 132.15 / GN 132.25 are based on two-way connector clamps. The additionally provided mounting holes are used to connect to the drive key of a linear actuator. Bores with the designation "G" are equipped with sleeve bearings.

With the screw locations **z**, the play of the guide bores **d<sub>1</sub>** / (**d<sub>2</sub>**) can be adjusted or the linear actuator connectors can be clamped after adjustment. Type B is equipped with seals at the screw locations.

For quick clamping without tools, the cap nuts can be replaced by the adjustable hand levers GN 911.3 listed in the table as accessories.

see also...

- *Stainless Steel Construction Tubes GN 990* → Page 1835
- *Linear Actuators GN 291* → Page 1950

How to order (For one-axis system)

<b>GN 132.15-G30-B30-A-4</b>	1 <b>d<sub>1</sub> - d<sub>2</sub></b>
	2 <b>Type</b>
	3 <b>Identification no.</b>

How to order (For two-axis system)

<b>GN 132.25-G50-G50-B-4</b>	1 <b>d<sub>1</sub> - d<sub>2</sub></b>
	2 <b>Type</b>
	3 <b>Identification no.</b>