



ELESA original design CFA-ERS

**3 Type**

**C** 2x2 bores for countersunk screws

**1**

**2**

l <sub>1</sub>		l <sub>2</sub>		d <sub>1</sub>	d <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	l <sub>3</sub>	l <sub>4</sub>	m <sub>1</sub> ±0,25	m <sub>2</sub> ±0,25
Nominal dimension	Actual dimension	Nominal dimension	Actual dimension											
48	48	49	49,5	5,5	4	19	11	13	36	26	44	17	31	30
64	64	65	65	6,5	5	23	13,5	15	36	30	44	24	40	40
98	97,5	98	96,5	10,5	8	35	20,5	23	48	46	63	35	62,5	59,5

**Specification**

- Plastic (Polyamide PA)
  - black, matte
  - temperature resistant up to 80 °C
- Pin
  - Steel, blackened
- Hand levers GN 604.2
  - Plastic (Polyamide PA)
  - black
- *Plastic characteristics* → Page 1483
- *Load rating information* → Page XYZ
- RoHS

**Information**

With hinges GN 151.2, doors, flaps etc. can be locked in any position. When not operated, this clamping lever is not connected to the thread of the hinge pin and it is in a „free-wheel“ position. By pushing down the centre button of the lever it engages itself in two notches and the hinge can be tightened or loosened. It prevents this hinge from being moved accidentally and in addition it ensures that this lever will never interfere with the movement of this lever.

see also...

- Hinges GN 151 (not adjustable) → Page 967

How to order

**GN 151.2-64-65-C**

- 1** l<sub>1</sub>
- 2** l<sub>2</sub>
- 3** Type