



<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub> H9	<sup>2</sup> d <sub>3</sub>	<sup>3</sup> Length l			d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	t min.
44	B 6	M 6	10	20	-	17	24	10	13
44	-	M 8	16	30	50	17	24	10	13
54	B 8	M 8	16	30	50	20	30	12,5	18
54	-	M 10	20	30	50	20	30	12,5	18

**Specification**

- Base body  
Plastic  
Technopolymer (Polypropylen PP)
- Softline coating  
- Elastomer (TPE) 70 Shore A  
- Chemically bonded with base body  
- FDA compliant plastic granulate  
- Temperature resistant up to 80 °C  
- Black, matte finish
- Bushing  
Brass
- Threaded stud  
Steel zinc plated, blue passivated
- ISO Fundamental Tolerances → Page 2151
- Plastic Characteristics → Page 2158
- RoHS

**Information**

The softline coating makes the knurled knobs GN 4534 particularly user-friendly and ergonomic.

The **soft, slip-proof** contact area improves the contact both in hot (hand perspiration) and in dry ambient conditions, in the event of oily surfaces and even high or low temperatures.

The use of knurled knobs is recommended particularly when frequent or heavy duty clamping is required.

see also...

- Product Family Softline → Page 18
- Knurled Knobs GN 534 → Page 622
- Knurled Screws GN 534 → Page 623

How to order (Bushing)	
<sup>1</sup> d <sub>1</sub>	1
<sup>2</sup> d <sub>3</sub> (d <sub>2</sub> )	2
<b>GN 4534-54-M10</b>	

How to order (Threaded stud)	
<sup>1</sup> d <sub>1</sub>	1
<sup>2</sup> d <sub>3</sub>	2
<sup>3</sup> Length l	3
<b>GN 4534-44-M8-16</b>	