



1.1

1.2

1.3

1.4

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub> Thread	<sup>2</sup> d <sub>3</sub> H9 Bore	b	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub> ≈	t min.
63	M 6	B 6	7	16	41	12	12
63	M 8	B 8	7	16	41	12	16
80	M 8	B 8	9	21	52	15	16
80	M 10	B 10	9	21	52	15	20
100	M 10	B 10	11	25	65	19	20
100	M 12	B 12	11	25	65	19	24

**Specification**

- Stainless steel
- AISI 316
- Matte shot-blasted finish **MT**
- Polished finish **PL**
- *ISO Fundamental Tolerances* → Page QVX
- *Stainless Steel Characteristics* → Page QVX
- RoHS

<sup>3</sup>

**Information**

Stainless steel T-handles GN 5063 are great for lifting, moving or switching parts or to clamp them by means of threads. The ergonomic shape allows for high operating forces.

The T-handles can also be used in particularly aggressive environments thanks to the materials used.

see also...

- *T-Handles GN 563 (Plastic)* → Page QVX
- *T-Handle Screws GN 563.1 (Plastic)* → Page QVX
- *T-Handles GN 563.2 (Aluminum)* → Page QVX
- *Stainless Steel Wing Nuts GN 8340* → Page QVX
- *Stainless Steel Wing Screws GN 8350* → Page QVX

2.1

2.2

2.3

2.4

How to order	1
<sup>1</sup> d <sub>1</sub>	d <sub>1</sub>
<sup>2</sup> d <sub>2</sub> (d <sub>3</sub> )	d <sub>2</sub> (d <sub>3</sub> )
<sup>3</sup> Finish	Finish

**GN 5063-80-M10-MT**