



1	2	3	4	d ₁	d ₂	b	d ₃	d ₄	d ₅	h ₁	h ₂ ≈	t min.
63	M 6	7		16			16,8	12	41	12	12	
80	M 8	9		21			21,8	17	52	15	16	
100	M 10	11		25			25,8	21	65	19	20	

Specification

3 4

- Stainless steel precision casting AISI 316
 - Matte finish ($R_a < 0.8 \mu\text{m}$) **MT**
 - Polished finish ($R_a < 0.8 \mu\text{m}$) **PL**
- Sealing ring
 - H-NBR Temperature resistant -25 °C to +150 °C **H**
 - EPDM Temperature resistant -40 °C to +120 °C **E**
 - Blue
 - Hardness 85 ±5 Shore A
 - FDA compliant
- *Plastic Characteristics* → Page QVX
- *Stainless Steel Characteristics* → Page QVX
- RoHS

Information

T-handles GN 5064 are intended for use in hygienic areas. The sealed mounting surface enables mounting without dead spaces; the impervious geometry in combination with the high quality finish prevents the accumulation of dirt and facilitates cleaning.

T-handles are great for lifting, moving and operating parts or for clamping purposes by means of threads. The ergonomic shape allows for high operating forces.

The T-handles can also be used in particularly aggressive environments thanks to the material used.

see also..

- *Product Family Hygienic Design* → Page QVX
- *T-Handles GN 563.2 (Aluminum)* → Page QVX
- *T-Handles GN 5063 (Stainless Steel)* → Page QVX
- *Wing Nuts GN 8341 (Stainless Steel, Hygienic Design)* → Page QVX

Accessory

- Sealing Rings GN 7600 → Page QVX

How to order

1 d₁
2 d₂
3 Finish
4 Material (Sealing ring)

GN 5064-63-M6-PL-E

1.1

1.2

1.3

1.4

2.1

2.2

2.3

2.4

2.5