



- 2** Type
- SCK** With wing knob (same lock)
- SCT** With T-Handle (same lock)

3 **4**

h_1	Latch arm distance A											h_2	s max.
30	16	20	25	28	32	36	40	44	48	52	57	40	20
30	18	22	26	30	34	38	42	46	50	54	62	40	20
40	26	30	35	38	42	46	50	54	58	62	67	50	30
40	28	32	36	40	44	48	52	56	60	64	72	50	30
50	36	40	45	48	52	56	60	64	68	72	77	60	40
50	38	42	46	50	54	58	62	66	70	74	82	60	40
60	46	50	55	58	62	66	70	74	78	82	87	70	50
60	48	52	56	60	64	68	72	76	80	84	92	70	50

Specification

- Lock housing
Zinc die casting **ZD**
Housing collar
Powder coated
Black, RAL 9005, textured finish **● SW**
- Operating elements
Plastic (Polyamide PA)
Black, matte finish
- Key
Nickel silver with plastic hand piece
- Other parts
Steel, zinc plated, blue passivated
- Protection class IP65
- IP Protection Classes → Page QVX
- Plastic Characteristics → Page QVX
- RoHS

Accessory

- Protective Guide Plates GN 120.2 → Page QVX

Information

Lockable latches GN 515 are identical to standard latches GN 115 except for the extended housing. They are operated with a rotation limited to 90°, which moves the latch arm into the locked position behind the frame. The bevels of the latch arm ease the closing of the door.

By installing latch arms with different bend profiles, the latch distance A can be varied from 16 to 92 mm depending on the housing height h_1 , while the extended housing is suitable for a door thickness s up to 50 mm.

The latches each come with 2 keys and loosely enclosed latch arm. The key can be removed in both end positions. The lock is standard, so that every lock can be opened with the same key.

see also...

- Construction and Assembly Instructions → Page XYZ

How to order

1	Material
2	Type
3	h_1
4	Latch arm distance A
5	Finish

GN 515-ZD-SCK-40-38-SW

