



elasa
Original design VDN.FP-SST-A



2 Bore code

- B** Without keyway
- K** With keyway

4 Type

- A** Without handle
- D** With revolving handle

1 3

d ₁	d ₂ H7 Bore		d ₃	d ₄		d ₅		d ₆		d ₇	b		l ₁	l ₂		l ₃	l ₄	r	Ø Handle	
	Type A	Type D		Type A	Type D	Type A	Type D	Type A	Type D		Type A	Type D		Type A	Type D					
80*	10	12	20	18	-	28	-	43	-	30	14	-	10	28	-	31	-	-	-	
100	10	12	24	22	20	35	35	54	54	39	15	21	12	36	33,5	40	46	50	39	21
125	12	14	32	26,5	26,5	44	44	70	70	46	15	28	15	38	38	44	57	65	50	23
150	14	16	32	26,5	26,5	44	50	70	80	48	18	30	15	38	38	49	61	65	62	23
200	18	20	40	33	33	55	55	90	90	60	21	32	15	43	43	58	68	90	82	28
250	22	24	49	40	40	66	66	110	110	70	25	36	15	44	44,5	65	76	90	106	28
300	26	-	58	58	58	94	94	148	148	82	25	36	18	56	56	75	87	90	132	28

* only available in Type A

Specification

- Plastic
Duroplast (Phenolic PF)
- Reinforced
- Temperature resistant up to 110 °C
- Hub bushing
Stainless steel AISI 303
- Threaded bushing
Stainless steel AISI 303
- Handle GN 598.1
Plastic, Duroplast
Spindle
Stainless steel AISI 303
- Keyway P9 DIN 6885 Page 1 → Page 2078
- Cross Holes GN 110 → Page 2080
- ISO Fundamental Tolerances → Page 2151
- Plastic Characteristics → Page 2158
- RoHS

On request

- Without hub bore

Information

Disk handwheels GN 520.2 are renowned in particular for the matte passivated aluminum ring in the front.

The tough, reinforced black plastic (Duroplast PF) and high gloss polished surface give the disk handwheels a touch of elegance.

The ergonomic handle is easy to grasp and makes the disc handwheels easier to use.

This standard replaces the previous handwheels GN 520.6.

see also...

- *Stainless Steel Countersunk Washers GN 184.5 (for Axial Fixing)*
→ Page 1090
- *Disk Handwheels GN 521.5 (Plastic, Hub Bushing Stainless Steel)*
→ Page 255

How to order

GN 520.2-100-K12-D

- 1** d₁
- 2** Bore code
- 3** d₂
- 4** Type