



2 Bore code

- B** Without keyway
- K** With keyway

4 Type

- A** Without handle
- R** With revolving handle

1

3

d ₁	d ₂ H7 Bore	d ₃	d ₄	d ₅	b	l ₁	l ₂	l ₃	r	Ø Handle
80	8	10	18	20,5	25	18	17	35	29	16
100	10	12	18	20,5	25,5	20	17	37	37	18
125	12	14	22	26	31	22	22	44	48	22
160	14	16	26	31	40	25	27	51	65	23
200	16	20	30	36	48,5	28	34	61	84	24
250	20	24	35	44	58	32	38	69	105	25
300	20	26	40	52	66	35,5	43	78	127	25
375*	26	-	35	70	81	39	43	87	160	25

* not available from stock, requires a minimum order quantity

Specification

- Plastic Technopolymer (Polypropylene PP)
 - Reinforced, shock-resistant
 - Temperature resistant up to 80 °C
 - Black, matte finish
- Hub bushing Steel, blackened
- Threaded bushing Brass
- Revolving handles
 - Plastic, Technopolymer (Polyamide PA) Black, matte finish
 - Spindle steel Zinc plated, blue passivated
- Keyway P9 DIN 6885 Page 1 → Page 2078
- Cross holes GN 110 → Page 2080
- ISO Fundamental Tolerances → Page 2151
- Plastic Characteristics → Page 2158
- RoHS

Information

Elegant design and ergonomic requirements are realised for the spoked handwheels GN 522.

see also...

- Countersunk Washers GN 184 (for Axial Fixing) → Page 1090

How to order

GN 522-125-B 12-R

1	d ₁
2	Bore code
3	d ₂
4	Type