



b	Length l ±0,25									a	d	h	r	t min.
	SW / RS / SR / EL / BL			SMA / WSA										
20	100	112	117	120*	-	-	100	112	-	13	M 6	49	13	10
20	128	160	180*	200	235*	-	128	160	-	13	M 6	51	13	10
26	112	117	120	125	128	-	128	-	-	17	M 8	55	17	12
26	160	179	192	300	400	500	160	192	300	17	M 8	57	17	12

\* suitable for 19" rack and enclosure layout

**Specification**

- Aluminium
  - Powder coated, textured finish
    - Black, RAL 9005 ● **SW**
    - UV-resistant
    - Red, RAL 3000 ● **RS**
    - Silver, RAL 9006 ● **SR**
  - Powder coated, antimicrobial finish
    - Black, RAL 9005 ● **SMA**
    - White, RAL 9016 ○ **WSA**
  - Anodized, natural color ● **EL**
  - Plain, tumbled ○ **BL**
- Load Rating Information → Page 2106
- RoHS

**Information**

Cabinet U-handles GN 565 are manufactured from a bent aluminum profile and have excellent stability and ergonomic design.

In addition to the standard surfaces, these cabinet U-handles are also available with a functional coating.

The **SW** version is coated with a highly weather-resistant and UV-resistant powder coating system, making this version excellent for outdoor use.

The **SMA / WSA** versions have a powder coating based on silver ions, which gives them antimicrobial properties. The principle of action has been shown to reduce the contamination of the handle surfaces within 24 hours so that fewer than 1% of bacteria and fewer than 5% of viruses ultimately survive.

Standard parts with antimicrobial plastic coating are primarily used in the health care sector and in public buildings, such as airports, train stations, stadiums, etc.

see also...

- Product Family Sanline → Page 2154
- Inclined Cabinet U-Handles GN 565.2 (Aluminum, Mounting from the Back or the Operator's Side) → Page 114
- Stainless Steel Cabinet U-Handles GN 565.5 (Mounting from the Back or the Operator's Side) → Page 108

How to order	1	b
<b>GN 565-20-100-SW</b>	2	Length l
	3	Finish