



¹ l ₁	² d ₁ Thread	² d ₂ H9 Bore	² s H9 Square	³ l ₂	d ₃	d ₄	d ₅	e	h ₁	h ₂	h ₃	t ₁ min.	t ₂ min.
44	M 5	-	-	-	15,5	-	-	-	19	26,5	19	12	-
44	M 6	B 6	V 5	16	15,5	3	M 4	7	19	26,5	19	12	15
63	M 8	B 8	V 6	25	19	4	M 4	8	24,5	35	26,5	13	20
78	M 10	B 10	V 8	30	23	4	M 5	9	29,5	42	32	17	25
95	M 12	B 12	V 10	50	26,5	5	M 5	10	34	51,5	40	20	30

Specification

- Plastic
Technopolymer (Polyamide PA)
- Glass fiber reinforced
- Temperature resistant up to 130 °C
- Black-gray RAL 7021, matte finish
- Bushing
Brass
- Threaded stud
Steel
Zinc plated, blue passivated
- Grub screw DIN 916
Steel, blackened
- ISO Fundamental Tolerances → Page 2151
- Plastic Characteristics → Page 2158
- RoHS

Information

Design and handling of the clamping levers GN 601 comply with the requirements and claims of the Ergostyle® product family.

see also...

- Product Family Ergostyle® → Page 18
- Adjustable Clamping Levers GN 604 → Page 460 / 461

How to order (With / without bushing)

GN 601-44-V5

¹ l ₁
² s (d ₁ , d ₂)

How to order (With threaded stud)

GN 601-63-M8-25

¹ l ₁
² d ₁
³ l ₂

