



1.1

1.2

1.3

1.4

¹ $l_1 \pm 0,5$	² d_1 Thread	² d_2 Bore	b	h	l_2	l_3	s	t min.
88	M 5	B 4,5	13,5	36,5	112	74,5	9	10
120	M 5	B 4,5	15	42	144	106,5	11	10

2.1

Specification

- Plastic Technopolymer (Polyamide PA)
 - Glass fiber reinforced
 - Temperature resistant up to 130 °C
 - Black, matte finish
- Threaded bushing Brass
- *Strength Properties* → Page 2116
- *Plastic Characteristics* → Page 2158
- RoHS

Information

The dimensions of the cabinet U-handles GN 627 match 19" inserts. Cabinet U-handles GN 627 have been designed for fixing with sheet-metal screws with thread size ST 4.8, such as fillister-head screws DIN ISO 7049. The maximum recommended tightening torque is 5 Nm.

see also...

- *Cabinet U-Handles GN 427 (Aluminum, Ellipse Shaped Profile)* → Page 144
- *Stainless Steel Cabinet U-Handles GN 427.5 (Ellipse Shaped Profile)* → Page 144
- *Cabinet U-Handles GN 425 (Aluminum / Stainless Steel)* → Page 147

2.2

2.3

2.4

How to order	1
GN627-88-M5	l_1
	² $d_1 (d_2)$

