



3 Type

- A** Mounting from the back (threaded blind bore)
- B** Mounting from the operator's side

Distance bushing GN 628.2

1	2	2	5												
l_1	d_1 Type A	d_2 Type B	d_3	d_4	d_5	h_1	h_2	h_3	l_2	l_3 min.	s	A/F	t_1	t_2	
94 -1	M 5	-	22	22,5	6,5	35	-	18	116	72	7,5	-	10	-	
94 -1	M 6	6,5	22	22,5	6,5	35	17	18	116	72	7,5	10	12	6,5	
117 ±0,5	M 6	6,5	26	26,5	8,5	39	7	19,5	143	91	8,5	10	12	19,5	
117 ±0,5	M 8	8,5	26	26,5	8,5	39	18	19,5	143	91	8,5	13	13	8,5	
120 ±0,5	M 6	6,5	27	26,5	8,5	40,5	17,5	19,5	147	93	9,5	10	12	10,5	
120 ±0,5	M 8	8,5	27	26,5	8,5	40,5	17,5	19,5	147	93	9,5	13	13	10,5	
132 ±0,5	M 6	-	27	-	-	42	-	-	159	105	9,5	-	13	-	
132 ±0,5	M 8	8,5	27	26,5	8,5	42	17,5	19,5	159	105	9,5	13	13	10,5	
150 ±1	M 8	8,5	28	29	9	45	18	20,5	180	122	9,5	13	13	14	
179 ±1	M 8	8,5	29	29	9	51	19	20,5	208	150	9,5	13	13	16	
179 ±1	M 10	-	29	-	-	51	-	-	208	150	9,5	-	13	-	

Specification

- Plastic Technopolymer (Polyamide PA)
 - Glass fiber reinforced
 - Temperature resistant up to 130 °C
 - Black-gray, matte finish Similar RAL 7021
- Threaded bushing (Type A) Brass
- Color of the cover cap (matte finish):
 - Black-gray, RAL 7021
 - Orange, RAL 2004
 - Gray, RAL 7035
 - Yellow, RAL 1021
 - Blue, RAL 5024
 - Red, RAL 3000
 - Green, RAL 6017

- DSG
- DOR
- DGR
- DGB
- DBL
- DRT
- DGN

- Strength Properties → Page 2116
- Plastic Characteristics → Page 2158
- RoHS

4

Information

The design of the GN 628 cabinet U-handles matches the Ergostyle® product family.

The cover caps for type A are supplied ready assembled, for type B they are enclosed loose.

The „hand space“ can be enlarged with the distance bushings GN 628.2.

see also...

- Product Family Ergostyle® → Page 18
- Cabinet U-Handles GN 628.1 (Antibacterial Plastic) → Page 134
- Cabinet U-Handles GN 628.3 (Made of Flexible Plastic) → Page 135

How to order	
1	l_1
2	d_2 (d_1)
3	Type
4	Color of the cover cap

How to order (Distance bushing)	
5	h_3