



1

2

Length l	d <sub>1</sub> H9 Bore	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	t	Ø Knob
38	B 6	15,5	11	3	21	12,5	41	7	15	12
56	B 8	19	13,5	4	28,5	18,5	51,5	8	20	13
71	B 10	23	16	4	30	18	53	9	25	14,5

## Specification

3

- Body  
Plastic  
Technopolymer (Polyamide PA)
  - Glass fiber reinforced
  - Temperature resistant up to 80 °C
  - Black, RAL 9005, matte finish
- Hub bushing  
Brass
- Revolving knobs
  - Plastic, Technopolymer  
Black, matte finish
  - Spindle steel  
Zinc plated, blue passivated
- ISO Fundamental Tolerances → Page 2151
- Plastic Characteristics → Page 2158
- RoHS

## Information

The design of the cranked handles GN 670.2 matches the product family Ergostyle®.

Attaching the cranked handle on a shaft using a transverse pin or a set screw is made easier with the semilateral cross bore.

The finger recesses of the rotating cylinder head allows a safe grip and the ergonomic operation of the relatively small cranked handle.

see also...

- Product Family Ergostyle® → Page 18
- Cranked Handles GN 369.5 → Page 295

How to order

GN 670.2-38-B6-SW

1	Length l
2	d <sub>1</sub>
3	Color