


Fill symbol



Drain symbol



3 Type

- O Neutral
- E With DIN fill symbol
- A With DIN drain symbol

4 Identification no.

- 1 Without vent drilling

1

2

d ₁	d ₂	d ₃	e ≈	l ₁	l ₂	s	t
19	G 1/4	M 14 x 1,5	M 5	17,3	15,5	8	15
22	G 3/8	M 16 x 1,5	M 5	20,8	15,5	8	18
26	G 1/2	M 20 x 1,5	M 5	24,3	16	8,5	21
32	G 3/4	M 26 x 1,5	M 5	31,2	17	9	27
40	G 1	M 33 x 1,5	M 5	37	19,5	11	32

Specification

- Stainless steel AISI 316L
Precision turned, plain finish
- Seal
Fluoro-elastomer (FPM / FKM)
- Brown
- Temperature resistant up to 180 °C
- *Elastomer Characteristics* → Page QVX
- *Stainless Steel Characteristics* → Page QVX
- RoHS

On request

- Other thread sizes
- With dipstick
- With acrylonitrile butadiene rubber (NBR) seal GN 741.5

Information

Stainless steel threaded plugs GN 742.5 can be used in particularly aggressive environments thanks to the material used.

The seal is embedded in a radial recess and thus cannot be lost, squeezed out or overloaded during tightening.

The outer diameter d₁ of the stainless steel threaded plugs GN 742.5 is matched to screw-in holes for pipe fittings according to DIN 3852.

see also...

- *Threaded Plugs GN 741 / GN 742 (Aluminum)* → Page QVX / QVX
- *Threaded Plugs GN 749 (Steel, Zinc Plated)* → Page QVX
- *Threaded Plugs GN 740 / GN 747 (Plastic)* → Page QVX / QVX
- *Threaded Plugs GN 442 (Aluminum, with Wing Knob)* → Page QVX

How to order

1	d ₁
2	d ₂
3	Type
4	Identification no.

GN 742.5-40-M33X1,5-A-1

