



3 Type

- D with female thread
- E with threaded stud

1

2

2

| d ₁ | d ₂ Type D | d ₃ Type E | d ₄ | d ₅ | h | Length l | t min. |
|----------------|--------------------------|--------------------------|----------------|----------------|----|----------|-----------|
| 20 | M 5 | M 5 | 14 | 14,8 | 24 | 10 | 7 |
| 25 | M 6 | M 6 | 16 | 16,8 | 29 | 12 | 9 |
| 32 | M 8 | M 8 | 18 | 18,8 | 37 | 14 | 12 |

Specification

- Stainless Steel
 - AISI 316 L (A4)
 - matte (Ra < 0.8 µm)
 - polished (Ra < 0.8 µm)
- Sealing ring
 - hydrogenated acrylonitrile butadiene rubber (H-NBR)
 - blue
 - temperature resistant -25 °C to +150 °C
 - Hardness 85 ±5 Shore A
 - FDA compliant
- *Stainless Steel characteristics*
→ Main catalogue Page 1489
- **RoHS compliant**

4

MT
PL

Information

GN 75.6 waist shaped knobs are intended for use in hygiene areas. The sealed mounting surface enables mounting without dead spaces; the impervious geometry in combination with the high quality finish prevents the accumulation of dirt and facilitates cleaning.

GN 75.6 waist shaped knobs have a compact and timeless design.

see also...

- Sealing rings [Hygienic Design GN 7600](#) → Page 16

How to order

GN 75.6-25-M8-E-MT

- 1 d₁
- 2 d₃ (d₂)
- 3 Type
- 4 Finish