



ELESA Original design TN.

**2 Coding**

- 1 without vent hole
- 2 with vent hole



1				3					
d <sub>1</sub>		d <sub>2</sub> Vent hole	d <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	s	e ≈		
G 1/8	M 10 x 1,5	M 12 x 1,5	-	2	15	9	15	19	21,5
G 1/4	M 14 x 1,5	-	-	2	15	9	15	19	21,5
G 3/8	M 16 x 1,5	-	-	2	17,5	9	15	22	25
G 1/2*	M 18 x 1,5	M 20 x 1,5	-	2	21	11	18	26	29,5
G 3/4*	M 22 x 1,5	M 25 x 1,5	M 26 x 1,5	2	25	12	20	32	36,5
G 1*	M 35 x 1,5	-	-	2	31	13	22	38	44
G 1 1/4	M 40 x 1,5	-	-	2	38	14	24	46	52,5
G 1 1/2	-	-	-	2	46	15	26	55	63

\* These sizes are also available as GN 745.2 with O-ring instead of a flat seal.

**Specification**

- Plastic (Polyamide PA)
  - glass fibre reinforced
  - black, matt
  - temperature resistant up to 100 °C
- Sealing ring rubber NBR (Perbunan)
- *Elastomer characteristics* → Page 1140
- *Plastic characteristics* → Page 1141
- **RoHS compliant**

**Accessory**



**GN 745.1**  
neutral

**GN 747.1**  
with re-fill  
symbol

**GN 740.1**  
with drain  
symbol

**Information**

Suitable for threaded plugs GN 745 are self adhesive, matt anodized aluminium discs with graphic symbols (0.3 mm thick) which can be supplied.

see also...

- *Plugs GN 741 / GN 742 (Aluminium)* → Page 916

Plug with flat seal  <b>GN 745-G<sup>3</sup>/<sub>4</sub>-1</b>	1	d <sub>1</sub>
	2	Coding

Plug with O-ring  <b>GN 745.2-G<sup>1</sup>/<sub>2</sub>-1</b>	1	d <sub>1</sub>
	2	Coding

Aluminium disc  <b>GN 740.1-25</b>	3	d <sub>3</sub>
--	---	----------------

2.1  
2.2  
2.3  
2.4  
2.5  
2.6  
2.7  
2.8  
2.9