



- 2 Type**
KS Ball with male thread
KI Ball with female thread
- 3 Identification No.**
- 1 Mounting socket with female thread
 - 2 Mounting socket with male thread



d ₁	d ₂	d ₃	d ₄	l ₁	l ₂	l ₃	l ₄	l ₅ ^{+1.0 -0.3}	l ₆ ≈	l ₇ ≈	A/F ₁	A/F ₂	recommended tightening torque in Nm ≈
M 6	M 6	17	8,5	10	8	11	20	25	16,8	16	15	7	15
M 8	M 8	19	11	12	10	12,5	23	29,5	19,5	18	17	9	20
M 10	M 10	21	13	15	12	14	26	33,5	23,5	20	19	11	35
M 12	M 12	28	16	14	15	20	34	44	27,7	28	21	14	45

Specification

- Steel
zinc plated, blue passivated
- Brake piece
Technopolymer (Polyamide PA)
- **RoHS compliant**

Information

The clamping nut of the ball joints GN 782 can be set to give a required thrust on the Belleville spring washers in order to increase the resistance to the ball movement.

At the same time the Belleville spring washers act as safety washers for the screws.

Once the max. thrust to the Belleville spring washers is reached the ball arm is firmly immobilised in position over the clamping nut and screw.

How to order

GN 782-M10-KS-1

1	d ₁
2	Type
3	Identification No.

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9

